

Amendments to the Specification:

Please replace paragraph 4 on page 4 with the following amended paragraph:

A pressure chamber housing for a pressure chamber may be provided so that in use the pressure of fluid in the pressure chamber maintains the indexing surface ~~face~~ of the rotatable indexing member in connect with the indexing surface ~~face~~ of the fixed indexing member.

Please replace paragraph 6 on page 4 with the following amended paragraph:

The indexing surface ~~face~~ of the fixed indexing member may be the surface of an indexing plate.

Please replace paragraph 2 on page 10 with the following amended paragraph:

Referring now to figures 2, 5 and 6, the rotatable indexing member 26 is an annular disc with a bore 68 through which the extension member 44 of the fixed indexing member 28 extends, and about which extension member 44 the rotatable indexing member 26 is rotatable. The rotatable indexing member 26 has a pressure chamber surface 70 has a circumferentially extending lip 71 for inter-engagement with a pressure housing 72. A seal receiving step 74 is provided in the bore 68 for a seal for a pressure chamber 76. In use, the pressure of a fluid, which could be air or nitrogen for example, in the pressure chamber 76 maintains the indexing surface ~~face~~ 36 of the rotatable indexing member 26 in connect with an indexing surface ~~face~~ 36.1 of the fixed indexing member 28.